

# Specifications

Model	SR-6	SR-10	SR-18	SR-30
<b>BTU Input</b>				
Propane Gas	6,000 BTU	10,000 BTU	18,000 BTU	30,000 BTU
Natural Gas	6,000 BTU	10,000 BTU	18,000 BTU	30,000 BTU
Gas Inlet Size	3/8"	3/8"	3/8"	3/8"
<b>General Specs</b>				
Plaques	One Plaque	One Plaque	Three Plaques	Five Plaques
Thermostat	Manual (1 heat setting)	Manual (1 heat setting)	Manual (3 heat setting)	Manual (3 heat setting)
Ignition Control	Standing Pilot/Piezo	Standing Pilot/Piezo	Standing Pilot/Piezo	Standing Pilot/Piezo
Safety Control	O.D.S**	O.D.S**	O.D.S**	O.D.S**
<b>Overall Dimensions</b>				
Width	12"w x 6.5"d x 22"h	12"w x 6.5"d x 22"h	18"w x 6.5"d x 22"h	25"w x 6.5"d x 22"h
Weight	18 Lbs	18 Lbs	27 Lbs	35 Lbs
<b>Clearances</b>				
Top	24"	24"	36"	36"
Sides	6"	6"	6"	8"
Bottom to Floor	2"	2"	2"	2"
<b>Accessories</b>				
Blower	N/A	N/A	Model SRB-18	Model SRB-30
Floor Stand *	Model SRS-10	Model SRS-10	Model SRS-18	Model SRS-30

\* Floor stand can not be used in a bathroom or bedroom installation. SR-6 must be wall mounted in a bathroom or bedroom installation.

\* Floor stand can not be used in a bedroom installation. SR-10 must be wall mounted in a bedroom installation.

The bathroom or bedroom must be an unconfined space. ANSI Z223.1/NFPA54 defines an unconfined space as "a space whose volume is not less

\*\* Pilot Equipped with Automatic Shut-Off and Oxygen Depletion Sensor on All Models

Pilot light safety system turns the heater off if not enough fresh air is available.

Note: • Not all heater models are allowed by some local codes; i.e., vent-free. Be sure the heater model you have chosen is allowed in your area.

• At high altitudes additional heat may be required. • If you have a single room with 4 exterior walls, additional heat may be required.

ESN: 85922-070531-776360-56



© 2008 Alta Power Corp. All Rights Reserved.

